



Key Feature Set

- 1 Robust Design: Module withstands up to 7000 Pa (ca. 690 kg/m²) Snow / 4000 Pa (ca. 210 km/h) Wind loads *
- 2 Anti-PID: Modules are qualified to withstand PID related degradation **
- 3 Guaranteed Quality: 12 Year Workmanship and 25 Years linear Performance Warranty ***
- 4 Predictable Output: Positive Power Sorting of 0 to +5 Watt
- 5 Higher Yield: Module Current Sorting provides up to 2.5% more Energy
- 6 Innovative Solution: Anti-Reflection Glass with Self-Clean hydrophobic Layer
- 7 Harsh Environment: Verified against Salt Mist and Ammonia Corrosion (IEC 61701 and IEC 62716)
- 8 Weak Light: Excellent Performance even under low Irradiation

* Please refer to Hanwha Solar Module Installation Guide

** Test conditions: Module negatively charged with 1000 Volts at 25°C for 168 hours with Al-Foil coverage

*** Please refer to Hanwha Solar Product Warranty for details

Quality and Environmental Certificates

- ISO 9001 quality standards and ISO 14001 environmental standards
- OHSAS 18001 occupational health and safety standards
- IEC 61215 & IEC 61730 Application Class A certifications
- EN 13501-1 Class E fire test rating
- Conformity to CE (low Voltage Directive and EMI)



ID 0000040248

About Hanwha Solar

Hanwha Solar is a vertically integrated manufacturer of photovoltaic modules designed to meet the needs of the global energy consumer.

- High reliability, guaranteed quality, and excellent cost-efficiency due to vertically integrated production and control of the supply chain
- Optimization of product performance and manufacturing processes through a strong commitment to research and development
- Global presence throughout Europe, North America and Asia, offering regional technical and sales support

HSL 60 | Poly - Black Edition

Electrical Characteristics

Electrical Characteristics at Standard Test Conditions (STC)

Power Class	245 W	250 W	255 W	260 W	265 W
Maximum Power (P_{max})	245 W	250 W	255 W	260 W	265 W
Open Circuit Voltage (V_{oc})	37.4 V	37.7 V	38.0 V	38.1 V	38.3 V
Short Circuit Current (I_{sc})	8.70 A	8.79 A	8.89 A	8.93 A	8.97 A
Voltage at Maximum Power (V_{mpp})	30.1 V	30.4 V	30.8 V	31.2 V	31.5 V
Current at Maximum Power (I_{mpp})	8.15 A	8.23 A	8.29 A	8.35 A	8.42 A
Module Efficiency (%)	15.1 %	15.5 %	15.8 %	16.1 %	16.4 %

P_{max} , V_{oc} , I_{sc} , V_{mpp} , and I_{mpp} tested at Standard Testing Conditions (STC) defined as irradiance of 1000W/m² at AM 1.5 solar spectrum and a temperature of 25±2°C. Module power class have positive power sorting: 0 to +5W. Measurement tolerance: ±3% (P_{max})

Electrical Characteristics at Normal Operating Cell Temperature (NOCT)

Power Class	245 W	250 W	255 W	260 W	265 W
Maximum Power (P_{max})	179 W	183 W	186 W	189 W	195 W
Open Circuit Voltage (V_{oc})	34.8 V	35.0 V	35.2 V	35.4 V	35.5 V
Short Circuit Current (I_{sc})	7.05 A	7.13 A	7.22 A	7.29 A	7.31 A
Voltage at Maximum Power (V_{mpp})	27.3 V	27.6 V	27.9 V	28.1 V	28.7 V
Current at Maximum Power (I_{mpp})	6.56 A	6.64 A	6.67 A	6.76 A	6.82 A

P_{max} , V_{oc} , I_{sc} , V_{mpp} , and I_{mpp} tested at Normal Operating Cell Temperature (NOCT, 45±3°C) defined as Irradiance of 800W/m²; Ambient temperature 20°C; Wind speed 1m/s. Measurement tolerance: ±3% (P_{max})

Temperature Characteristics

Normal Operating Cell Temperature (NOCT)	45±3°C
Temperature Coefficients of P	- 0.43 % / °C
Temperature Coefficients of V	- 0.31 % / °C
Temperature Coefficients of I	+ 0.05 % / °C

Maximum Ratings

Maximum System Voltage	1 000 V (IEC)
Series Fuse Rating	15 A
Maximum Reverse Current	Series fuse rating multiplied by 1.35

Mechanical Characteristics

Dimensions	1636 mm × 988 mm × 40 mm
Weight	19±0.5kg
Frame	Aluminum-alloy, anodized
Front	3 mm tempered anti-reflection glass
Encapsulant	EVA
Back Cover	Composite sheet
Cell Technology	Polycrystalline
Cell Size	156 mm × 156 mm (6 in × 6 in)
Number of Cells (Pieces)	60 (6 × 10)
Junction Box	Protection class IP 67; 3 sets of diodes
Output Cables	Solar cable: 4 mm ² ; length: 1000 mm
Connector	Amphenol H4

System Design

Operating Temperature	- 40 °C to 85 °C
Hail Safety Impact Velocity	25 mm at 23 m/s
Fire Safety Classification (IEC 61730)	Class C
Static Load Wind/Snow	4000 Pa / 7000 Pa

Packaging and Storage

Storage Temperature	- 40 °C to 85 °C
Packaging Configuration	24 pieces per pallet
Loading Capacity (40 ft. HQ Container)	672 pieces

Nomenclature:

HSL60P6-PB-1-xxx B
xxx represents the power class

Performance at Low Irradiance:

The typical efficiency at 200 W/m² in relation to 1000 W/m², (25°C, AM 1.5) is at least 96 % of STC efficiency.

