

SMT Series Datasheet



Technical Data	GW25K-MT	GW30K-MT	GW36K-MT
PV String Input Data			
Max. DC Input Power (Wp)	32500	39000	42900
Max. DC Input Voltage (V)	1100	1100	1100
MPPT Range (V)	200~950	200~950	200~950
Start-up Voltage (V)	180	180	180
Nominal DC Input Voltage (V)	600	600	600
Max. Input Current (A)	25/25/25	25/25/25	25/25/25
Max. Short Current (A)	31.3/31.3/31.3	31.3/31.3/31.3	31.3/31.3/31.3
No. of MPP Trackers	3	3	3
No. of Input Strings per Tracker	2/2/2	2/2/2	2/2/2
AC Output Data			
Nominal Output Power (W)	25000	30000	36000* ¹
Max. Output Power (W)	27500* ²	33000* ²	36000* ²
Max. Output Apparent Power (VA)	27500* ³	33000* ³	36000* ³
Nominal Output Voltage (V)		400, 3L/N/PE or 3L/PE	
Nominal Output Frequency (Hz)	50/60	50/60	50/60
Max. Output Current (A)	40	48	53.3
Output Power Factor		~1 (Adjustable from 0.8 leading to 0.8 lagging)	
Output THDi (@Nominal Output)	<3%	<3%	<3%
Efficiency			
Max. Efficiency	98.7%	98.8%	98.8%
European Efficiency	>98.4%	>98.5%	>98.5%
Protection			
Anti-islanding Protection	Integrated	Integrated	Integrated
Input Reverse Polarity Protection	Integrated	Integrated	Integrated
PV String Current Monitoring	Integrated	Integrated	Integrated
Anti-PID Function for Module	Optional	Optional	Optional
Insulation Resistor Detection	Integrated	Integrated	Integrated
DC Surge Protection		Type III (Type II optional)	
AC Surge Protection		Type III (Type II optional)	
Residual Current Monitoring Unit	Integrated	Integrated	Integrated
Output Over Current Protection	Integrated	Integrated	Integrated
Output Short Protection	Integrated	Integrated	Integrated
Output Over Voltage Protection	Integrated	Integrated	Integrated
AFCI	Optional	Optional	Optional
Terminal Temperature Detection	Optional	Optional	Optional
General Data			
Operating Temperature Range (°C)	-30~60	-30~60	-30~60
Relative Humidity	0~100%	0~100%	0~100%
Operating Altitude (m)	≤3000	≤3000	≤3000
Cooling	Fan Cooling	Fan Cooling	Fan Cooling
User Interface		LCD & LED or APP & LED	
Communication		RS485 or WiFi or GPRS or PLC	
Weight (kg)	40	40	40
Size (Width*Height*Depth mm)	480*590*200	480*590*200	480*590*200
Protection Degree	IP65	IP65	IP65
Night Self Consumption (W)	<1	<1	<1
Topology		Transformerless	

*¹: 33kW for Italy, 36kW for other countries.

*²: For Belgium Max. Output Power (W): GW25K-MT is 25000; GW30K-MT is 30000; GW36K-MT is 36000.

*³: For Belgium Max. Output Apparent Power (VA): GW25K-MT is 25000; GW30K-MT is 30000; GW36K-MT is 36000.

*: Please visit GoodWe website for the latest certificates.