

# SOFAR 20K~33KTL-G2

20000/ 25000/ 30000/ 33000



## Three-Phase Dual-MPPT

- 4"** Super large 4-inch LCD
- 1100V** 1100V voltage level design
- DRM** Built-in DRM port and logic
- 98.6%** Max. efficiency up to 98.6%
- I-V** I-V curve scanning function
- +** Built-in SPD, over / under voltage, over current, over temperature, Anti-islanding and other multiple protections

### Datasheet

	SOFAR 20000TL-G2	SOFAR 25000TL-G2	SOFAR 30000TL-G2	SOFAR 33000TL-G2
<b>Input (DC)</b>				
Recommended Max. PV input power	26600Wp	33250Wp	39900Wp	43890Wp
Max DC power for single MPPT	13000W	16000W	18000W	20000W
Number of MPP trackers	2			
Number for DC inputs	2 for each MPPT	3 for each MPPT	3 for each MPPT	3 for each MPPT
Max. input voltage	1100V			
Start-up voltage	250V			
Rated input voltage	620V			
MPPT operating voltage range	230V-960V			
Full power MPPT voltage range	480V-850V	460V-850V	520V-850V	580V-850V
Max. input MPPT current	24A/24A	28A/28A	30A/30A	30A/30A
Maximum DC input short circuit current per MPPT	30A	35A	37.5A	37.5A
<b>Output (AC)</b>				
Rated power	20000W	25000W	30000W	33000W
Max. AC power	22000VA	27500VA	33000VA	36300VA
Max. Output current	32A	40A	48A	53A
Nominal grid voltage	3/N/PE, 220/380Vac, 230/400Vac, 240/415Vac			
Grid voltage range	310Vac-480Vac (According to local standard)			
Nominal frequency	50/60Hz			
Grid Frequency range	45Hz-55Hz/54Hz-66Hz (According to local standard)			
Active power adjustable range	0~100%			
THDi	< 3%			
Power factor	> 0.99 (adjustable +/-0.8)			
<b>Performance</b>				
Max efficiency	98.2%	98.4%	98.4%	98.6%
European weighted efficiency	98.0%	98.2%	98.2%	98.2%
Self-consumption at night	< 1W			
MPPT efficiency	> 99.9%			
<b>Protection</b>				
DC reverse polarity protection	Yes			
DC switch	Yes			
Protection class/ overvoltage category	I/III			
Safety protection	Anti islanding, RCMU, Ground fault monitoring			
ARPC	Anti reverse power controller (optional)			
<b>Communication</b>				
Power management unit	According to certification and request			
Standard communication mode	RS485, Wifi/Ethernet/GPRS(optional), SD card			
Operation data storage	25 years			
<b>General Data</b>				
Ambient temperature range	-25°C~ +60°C			
Topology	Transformerless			
Degree of protection	IP65			
Allowable relative humidity range	0~100%			
Max. operating altitude	2000m			
Noise	<30dB	<45dB	<45dB	<45dB
Weight	37kg			
Cooling	Natural	Fan	Fan	Fan
Dimension	666*512*254mm			
Display	LCD display			
Warranty	5 years/ 7 years/ 10 years			
<b>Standard</b>				
EMC	EN 61000-6-2, EN 61000-6-3, EN 61000-3-11, EN 61000-3-12			
Safety standards	IEC62109-1/2, IEC62116, IEC61727, IEC-61683, IEC60068(1,2,14,30), IEC60255			
Grid standards	AS/NZS 4417, VDE V 0124-100, V 0126-1-1, VDE-AR-N 4105, CEI 0-21/CEI 0-16, EN 50549, G59, P.O. 12.3, RD1699, UTE C15-712-1, EN 50530, NB/T32004			