


Mono PERC 182mm 108 Cells


MS(390-410)MB-54H Black Frame

390/395/400/405/410 WP




High customer value

- Lower LCOE (Levelized Cost Of Energy), reduced BOS (Balance Of System) cost, shorter payback time
- Lower guaranteed first year and annual degradation
- Designed for compatibility with existing mainstream system components
- Higher return on Investment




High energy yield

- Excellent IAM (Incident Angle Modifier) and low irradiation performance, validated by 3rd party certifications
- The unique design provides optimized energy production under inter-row shading conditions



High reliability

- Minimized micro-cracks with innovative non-destructive cutting technology
- Ensured PID resistance through cell process and module material control
- Resistant to harsh environments such as salt, ammonia, sand, high temperature and high humidity areas
- Mechanical performance up to 5400 Pa positive load and 2400 Pa negative load
- Class-C fire safety test passed




High power up to 410W

- Large area cells based on 182mm silicon wafers and 1/2-cut cell technology
- Up to 21.00% module efficiency with high density interconnect technology
- Multi-busbar technology for better light trapping effect lower series resistance and improved current collection

APPLICATIONS >>



On-grid residential roof-tops



On-grid commercial/ industrial roof-tops




MAXIMUM EFFICIENCY




21.00%

POSITIVE POWER TOLERANCE


0 ~ +5W




DIMENSIONS OF PV MODULE(mm)



I-V CURVES OF PV MODULE(410W)



P-V CURVES OF PV MODULE(410W)



ELECTRICAL DATA (STC)

Parameter	390	395	400	405	410
Peak Power Watts- P_{MAX} (Wp)*	390	395	400	405	410
Power Tolerance- P_{MAX} (W)	0 ~ +5				
Maximum Power Voltage- V_{MPP} (V)	30.22	30.32	30.42	30.52	30.62
Maximum Power Current- I_{MPP} (A)	12.91	13.03	13.15	13.27	13.39
Open Circuit Voltage- V_{OC} (V)	36.10	36.18	36.27	36.35	36.42
Short Circuit Current- I_{SC} (A)	13.64	13.71	13.78	13.85	13.92
Module Efficiency η_m (%)	20.18	20.23	20.48	20.74	21.00

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5. *Measuring tolerance: ±3%.

ELECTRICAL DATA (NOCT)

Parameter	290	294	298	301	305
Maximum Power- P_{MAX} (Wp)	290	294	298	301	305
Maximum Power Voltage- V_{MPP} (V)	28.11	28.26	28.42	28.56	28.72
Maximum Power Current- I_{MPP} (A)	10.33	10.40	10.47	10.55	10.62
Open Circuit Voltage- V_{OC} (V)	34.76	34.83	34.90	34.98	35.05
Short Circuit Current- I_{SC} (A)	11.01	11.07	11.13	11.19	11.24

NOCT: Irradiance at 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s.

MECHANICAL DATA

Solar Cells	Monocrystalline
Cell Orientation	108 cells
Module Dimensions	1722×1134×30 mm (67.8×44.65×1.18 inches)
Weight	22 kg
Glass	3.2mm, Anti-Reflection Coating, High Transmission, Low Iron, Tempered Glass
Encapsulant Material	EVA/POE
Backsheet	White
Frame	30 mm(1.18 inches) Black, Anodized Aluminium Alloy
J-Box	IP 68 rated (3 bypass diodes)
Cables	Photovoltaic Technology Cable 4.0mm ² Portrait: N 300 or 1000mm / P 300mm or 1000mm Length can be customized
Connector	MC4 Compatible

*Please refer to regional datasheet for specified connector.

TEMPERATURE RATINGS

NOCT(Nominal Operating Cell Temperature)	43°C (±2°C)
Temperature Coefficient of P_{MAX}	- 0.34%/°C
Temperature Coefficient of V_{OC}	- 0.25%/°C
Temperature Coefficient of I_{SC}	0.04%/°C

MAXIMUM RATINGS

Operational Temperature	- 40 ~ +85°C
Maximum System Voltage	1500V DC (IEC)
	1000V DC (IEC)
Max Series Fuse Rating	25A

WARRANTY

- 15 year Product Workmanship Warranty
- 25 year Power Warranty
- 2.5% first year degradation
- 0.5% Annual Power Attenuation

*Please refer to product warranty for details.

PACKAGING CONFIGURATION

- Modules per pallet: 37pieces
- Modules per 40' container: 962 pieces



CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.

© 2021 Maysun Solar Co., Ltd. All rights reserved. Specifications included in this datasheet are subject to change without notice.

Website: www.maysunsolar.com