



NEW FROM SOLAX

X3-MIC-G2



X3-MIC-G2

3.0kW/4.0kW/5.0kW/6.0kW
8.0kW/10.0kW/12.0kW/15.0kW



Features

High-efficiency

- Maximum efficiency is up to 98.3%
- Low startup voltage, ultrawide MPPT voltage range
- 200% oversizing, 110% overloading output (Except 15kW model)
- Built-in shadow tracking function

Safe

- IP66 protection
- Integrated SPD

Smart

- Built-in export power control
- Remote setting and upgrading
- 24 hours operation monitoring
- Intelligent load management - heat pump (Optional)
- Multiple monitoring methods, Pocket Wi-Fi/LAN/4G (Optional)

Economic

- Ultra-high power density
- Maximum 16A DC input current, support high power solar panel

For More Informations Contact Us

info@solaxpower.com
service@solaxpower.com



www.solaxpower.com

AU: +61 1300 476529

DE: +49 6142 4091664

Global: +86 571-56260008

UK: +44 2476 586998

NL: +31 (0) 852 737932



X3-MIC G2 (THREE PHASE)

	X3-MIC-3K-G2	X3-MIC-4K-G2	X3-MIC-5K-G2	X3-MIC-6K-G2	X3-MIC-8K-G2	X3-MIC-10K-G2	X3-MIC-12K-G2	X3-MIC-15K-G2
DC INPUT								
Max. PV array input power [Wp]	6000	8000	10000	12000	16000	20000	24000	30000
Max. PV input voltage [V]	1000	1000	1000	1000	1000	1000	1000	1000
Startup voltage [V]	150	150	150	150	150	150	150	150
Nominal input voltage [V]	640	640	640	640	640	640	640	640
MPP tracker voltage range [V]	120~980	120~980	120~980	120~980	120~980	120~980	120~980	120~980
No. of MPP trackers/Strings per MPP tracker	2(1/1)	2(1/1)	2(1/1)	2(1/1)	2(1/1)	2(1/1)	2(2/1)	2(2/1)
Max. input current[A]	16/16	16/16	16/16	16/16	16/16	16/16	32/16	32/16
Max. short circuit current[A]	20/20	20/20	20/20	20/20	20/20	20/20	40/20	40/20
AC OUTPUT								
Nominal AC output power [W]	3000	4000	5000	6000	8000	10000	12000	15000
Nominal AC output current [A]	4.6/4.4	6.1/5.8	7.6/7.3	9.1/8.7	12.2/11.6	15.2/14.5	18.2/17.4	22.7/21.8
Max. AC output apparent power [VA]	3300	4400	5500	6600	8800	11000	13200	15000
Max. AC output current [A]	4.8	6.4	8.0	9.6	12.8	16.0	19.1	22.7
Nominal AC voltage [V]				220/380V, 230/400V, 3/N/PE				
Nominal grid frequency/Grid frequency [Hz]				50/60				
Displacement power factor				0.8 leading-0.8 lagging				
THDi (Rated power) [%]				<3				
SYSTEM DATA								
Max. efficiency [%]	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3
Euro efficiency [%]	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8
Standby consumption (night) [W]				<3				
Ingress protection				IP66				
Operating temperature range [°C]				-30~+60(Derating above 45)				
Max. operation altitude [m]				4000(Derating above 3000)				
Relative humidity [%]				0~100				
Typical noise emission [dB]	<30	<30	<30	<30	<45	<45	<50	<50
Storage temperature [°C]				-30~+60				
Dimensions(WxHxD) [mm]			342*434*144.5			342*434*156		
Weight [kg]	15.5	15.5	15.5	15.5	17	17	18	18
Cooling concept			Natural cooling			Smart fan cooling		
Communication interfaces			USB / RS485 / DRM / (Optional: Pocket WiFi/LAN/4G) / Adapter box(Optional)					
PROTECTION								
Over/under voltage protection					YES			
DC isolation protection					YES			
DC reverse protection					YES			
Grid monitoring					YES			
DC injection monitoring					YES			
Back feed current monitoring					YES			
Residual current detection					YES			
Anti-islanding protection					YES			
Over temperature protection					YES			
SPD (DC/AC)					Type III / Type III			
STANDARD								
Safety				IEC/EN 62109-1; IEC/EN 62109-2; NB/T 32004				
EMC				IEC/EN 61000; NB/T 32004				
Certification			VDE4105; EN 50549; AS 4777.2; VDE4105; IEC 61727; IEC 62116; IEC 61683; IEC 60068; EN 50530; NB/T 32004					

¹ Input 1 is optional with two strings(Max. input current: 32A, Max. short circuit current: 40A)

*V2.2. Information may be subject to modify without notice. 650.00003.00