



## M125HV

High-efficiency three-phase solar inverter for large ground-mounted systems.



High input voltage



Peak efficiency

- Easy to install under the modules
- Separate AC wiring box for added safety
- Reactive power compensation 24/7

- 1 MPP tracker for 20 module strings
- Optional wireless communication via Sub-1G
- Arc fault and reverse polarity protection, Anti-PID function

# 140 kVA solar inverter

Input (DC)	M125HV	Mechanical design	M125HV
Max. input voltage	1500 V <sub>DC</sub>	Connection type AC side	Screw bolts; wire cross-section: Cu 50 to 185 mm <sup>2</sup> , Alu 50 to 185 mm <sup>2</sup> ; cable diameter: 24 to 51 mm (4 wires)
Operating voltage range	860 to 1500 V <sub>DC</sub>	Connection type DC side	20 pairs of DC plugs Amphenol H4 Plus <sup>8)</sup>
Output (AC)	M125HV	Communication	M125HV
Max. apparent power <sup>3)</sup>	140 kVA	Communication interfaces	2 x RS485, 2 x dry contacts, 1 x external power-off, 6 x digital inputs, Wi-Fi (optional), Sub-1G (optional)
Max. active power	125 kW <sup>4)</sup>	Data visualization	DeltaSolar app, MyDeltaSolar Cloud
Nominal apparent power <sup>3)</sup>	125 kVA	Display of operating status	3 LEDs
Voltage range <sup>5)</sup>	600 V -36%/+15%, 3 phases + PE ( $\Delta$ )		
Max. current	135 A		
Frequency range <sup>5)</sup>	50/60 Hz $\pm$ 5 Hz		
Adjustment range of power factor	0.8 cap to 0.8 ind (1.0 to 0.9 at max. power)		
Total harmonic distortion (THD)	< 3% at nominal apparent power		
Consumption in night mode <sup>6)</sup>	< 3.5 W		
AC surge protection devices	Type 2 (EN 61463-11) replaceable; type 1 upgradeable		
General Specifications		Safety / Standards	M125HV
Delta model name	M125HV_111	Protection class	IP65
Peak efficiency	99.1%	Safety class	I
Efficiency EU	98.7%	Configurable trip parameters	Yes
Operating temperature range	-25 to +60°C	Insulation monitoring	Yes
Temperature range without power derating	-25 to +50 °C	Overload behavior	Current limitation, power limitation
Storage temperature range	-25 to +60°C	Anti-islanding protection/grid regulation	UTE C15-712, ERDF-RES-PRO_64E, VDE-AR-N 4110
Relative humidity	0 to 100%, non-condensing	EMC	EN 61000-6-2, EN 61000-6-3, EN 61000-3-11, EN 61000-3-12
Max. operating altitude	4000 m (above sea level)	Safety	IEC 62109-1/-2; CE compliance
Topology	Without transformer		
Standard warranty	5 years (warranty extension available upon request)		
Mechanical design	M125HV	<p>1) Environmental conditions: &lt; 0°C: 860 to 1450 VDC, &lt; 25°C: 860 to 1350 VDC, &lt; 40°C: 860 to 1250 VDC</p> <p>2) The value when the internal temperature of the inverter is 25 °C. At higher internal temperatures, the value may drop to 10 A.</p> <p>3) Cos Phi = 1 (VA = W)</p> <p>4) The active power can be limited.</p> <p>5) AC voltage and frequency range are programmed based on the respective country regulations.</p> <p>6) Night-time consumption with standby communication</p> <p>7) Mounting plate included in scope of delivery</p> <p>8) Included in scope of delivery</p>	
Dimensions (H x W x D)	900 x 663 x 334 mm		
Weight	80 kg		
Cooling	Replaceable fan module		
Mounting options	Wall mounting <sup>7)</sup> , ground mounting		
Disconnectors	2 mechanical DC disconnectors		