

# eSolar AIO3



Multifunction in One  
(Wi-Fi, Bluetooth, Ethernet)



OLED Screen



Bluetooth  
Connection



Real-time  
Data Reading

## eSolar AIO3 Datasheet

General parameters	
Connecting inverters No. [set]	1
Inverter communication port	RS232, USB
Remote communication port	Bluetooth / Wi-Fi / Ethernet
Data collection interval[min]	1~30 [Optional], 10 [standard]
Firmware update method	Serial port / Remote
Access data method	APP / Remote sever
Status display	OLED
Electric parameter	
Input voltage	DC 5~7 ( $\pm 5\%$ )
Static consumption [W]	<1
Max. instant consumption [W]	<8
Environment	
Operating temperature range	-40°C~+85°C
Storage temperature range	-45°C~+90°C
Dimensions [H*W*D][mm]	144*49*40
Weight [g]	84
Ingress protection	IP65
Others	
Mounting method	Plug-in+Screw lock
Warranty [Year]	2 [Standard] / 5 [Optional]

**GUANGZHOU SANJING ELECTRIC CO., LTD.**

Website: [www.saj-electric.com](http://www.saj-electric.com)

E-mail: [info@saj-electric.com](mailto:info@saj-electric.com)

Add:SAJ Innovation Park, No.9, Lizhishan Road, Science City, Guangzhou, Guangdong, P.R.China.

