



LR6-60PE 290~310M



Hi-MO1 High Efficiency Low LID Mono PERC Technology

10-year Warranty for Materials and Processing;
25-year Warranty for Extra linear Power Output



-0.55%

25-year Power
Warranty Annual
Power Attenuation
-0.55%

+4.10%

Complete System and Product Certifications

IEC 61215, IEC61730, UL1703
ISO 9001:2008: ISO Quality Management System
ISO 14001: 2004: ISO Environment Management System
TS62941: Guideline for module design qualification and type approval
OHSAS 18001: 2007 Occupational Health and Safety



* Specifications subject to technical changes and tests. LONGi Solar reserves the right of interpretation.

Positive power tolerance (0 ~ +5W) guaranteed

High module conversion efficiency (up to 19.0%)

Slower power degradation enabled by Low LID Mono PERC technology: first year <2%, 0.55% year 2-25

Better energy yield with excellent low irradiance performance and temperature coefficient

Solid PID resistance ensured by solar cell process optimization and careful module BOM selection

Adaptable to harsh environment: passed rigorous salt mist and ammonia tests

Robust frame (40mm) withstands mechanical loading of 5400Pa for snow load on front and 2400Pa for wind load on rear side

LONGi Solar

Room 201, Building 8, Sandhill Plaza, Lane 2290, Zuchongzhi Road, Pudong District, Shanghai, 201203
Tel: + 86-21-61047332 Fax: +86 21- 61047377 E-mail: module@longi-silicon.com
Facebook: www.facebook.com/LONGi Solar


Note: Due to continuous technical innovation, R&D and improvement, technical data above mentioned may be of modification accordingly. LONGi Solar have the sole right to make such modification at anytime without further notice; Demanding party shall request for the latest datasheet for such as contract need, and make it a consisting and binding part of lawful documentation duly signed by both parties.

LR6-60PE 290~310M

Design (mm)

Mechanical Parameters

Operating Parameters



Cell Orientation: 60 (6×10)
 Junction Box: IP67, three diodes
 Output Cable: 4mm², 1000mm in length
 Connector: MC4 or MC4 compatible
 Weight: 18.2kg
 Dimension: 1650×991×40mm
 Packaging: 26pcs per pallet

Operational Temperature: -40 C ~ +85 C
 Power Output Tolerance: 0 ~ +5 W
 Maximum System Voltage: DC1000V (IEC)
 Maximum Series Fuse Rating: 15A
 Nominal Operating Cell Temperature: 45±2 C
 Application Class: Class A

Electrical Characteristics

Model Number	LR6-60PE-290M		LR6-60PE-295M		LR6-60PE-300M		LR6-60PE-305M		LR6-60PE-310M	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (Pmax/W)	290	213.2	295	216.8	300	220.5	305	224.2	310	227.9
Open Circuit Voltage (Voc/V)	39.7	36.7	39.9	36.9	40.1	37.1	40.2	37.2	40.3	37.3
Short Circuit Current (Isc/A)	9.58	7.72	9.69	7.81	9.81	7.91	9.94	8.01	9.98	8.04
Voltage at Maximum Power (Vmp/V)	32.3	29.7	32.6	29.9	32.8	30.1	33.0	30.3	33.2	30.5
Current at Maximum Power (Imp/A)	8.98	7.18	9.05	7.24	9.15	7.32	9.24	7.39	9.35	7.48
Module Efficiency(%)	17.7		18.0		18.3		18.7		19.0	

STC (Standard Testing Conditions): Irradiance 1000W/m², Cell Temperature 25 C, Spectra at AM1.5

NOCT (Nominal Operating Cell Temperature): Irradiance 800W/m², Ambient Temperature 20 C, Spectra at AM1.5, Wind at 1m/s

Temperature Ratings (STC)


Temperature Coefficient of Isc	+0.057%/C
Temperature Coefficient of Voc	-0.286%/C
Temperature Coefficient of Pmax	-0.380%/C

Mechanical Loading


Front Side Maximum Static Loading	5400Pa
Rear Side Maximum Static Loading	2400Pa
Hailstone Test	25mm Hailstone at the speed of 23m/s

I-V Curve


Current-Voltage Curve (LR6-60PE-300M)



Power-Voltage Curve (LR6-60PE-300M)



Current-Voltage Curve (LR6-60PE-300M)



LONGi Solar

Room 201, Building 8, Sandhill Plaza, Lane 2290, Zuchongzhi Road, Pudong District, Shanghai, 201203
 Tel: +86-21-61047332 Fax: +86 21- 61047377 E-mail: module@longi-silicon.com
 Facebook: www.facebook.com/LONGi Solar

Note: Due to continuous technical innovation, R&D and improvement, technical data above mentioned may be of modification accordingly. LONGi Solar have the sole right to make such modification at anytime without further notice; Demanding party shall request for the latest datasheet for such as contract need, and make it a consisting and binding part of lawful documentation duly signed by both parties.