



CSI-40KTL-GI-HFL



CSI-50KTL-GI-HFL

CSI-60KTL-GI-H

THREE PHASE STRING INVERTER 40-60 KW

CSI-40KTL-GI-HFL | CSI-50KTL-GI-HFL CSI-60KTL-GI-H

Canadian Solar's grid-tied, transformer-less string inverters help to accelerate the use of three-phase string architecture for commercial rooftop and small ground-mount applications. An NRTL approved, cost-effective alternative to central inverters, these inverters are modular design building blocks that provide high yield and enable significant BoS cost savings. They provide up to 98.8% conversion efficiency, a wide operating range of 200-800 V_{DC}, and four MPPTs for maximum energy harvest.




Standard warranty, extension up to 15 years

KEY FEATURES

- Maximum efficiency of 99%, Maximum EU efficiency of 98.5%
- 4 MPPTs to achieve higher system efficiency
- Transformerless design
- High switching frequency and ultra fast MPPT (<5 sec.) for maximum efficiency over a wide load range

EFFICIENCY CURVE

CSI-60KTL-GI-H@480 Vac



HIGH RELIABILITY

- Advanced thermal design and convection cooling
- Built in over-voltage and over-current protection
- DC reverse polarity and AC short circuit protection

BROAD ADAPTIBILITY

- IP65 rated for outdoor application
- Utility interactive controls: Active power derating, reactive power control and over frequency derating
- Integrated DC load rated disconnect
- Wide MPPT range for flexible string sizing
- 90 degree installation angle
- Supports up to 8 DC string inputs (2 per MPPT)

CANADIAN SOLAR INC. is committed to providing high quality solar products, solar system solutions and services to customers around the world. As a leading PV project developer and manufacturer of solar modules with over 25 GW deployed around the world since 2001, Canadian Solar Inc. is one of the most bankable solar companies worldwide.

*For detailed information, please refer to the Installation Manual.

CANADIAN SOLAR INC.

545 Speedvale Avenue West, Guelph, Ontario N1K 1E6, Canada | www.canadiansolar.com

SYSTEM/TECHNICAL DATA

MODEL NAME	CSI-40KTL-GI-HFL	CSI-50KTL-GI-HFL	CSI-60KTL-GI-H
DC INPUT			
Max. PV Power	45 kW (13.5 kW/MPPT)	60 kW (16 kW/MPPT)	72 kW (22.5 kW/MPPT)
Max. DC Input Voltage	1000 V _{DC}	1100 V _{DC}	
Operating DC Input Voltage Range	200-1000 V _{DC}		
Start-up DC Input Voltage/Power	350 V	200 V	
Number of MPP Trackers	4		
MPPT Full Power Voltage Range	556-800 V _{DC}	568-850 V _{DC}	526-850 V _{DC}
Operating Current (Imp)	88 A (22 A per MPPT)		114 A (28.5 A per MPPT)
Max. Input Current (Isc)	137.2 A (34.3 A per MPPT)		178 A (44.5 A per MPPT)
Number of DC Inputs	8 (2 per MPPT)		12 (3 per MPPT)
DC Disconnection Type	Load rated DC switch		
AC OUTPUT			
Rated AC Output Power	40 kW	50 kW	60 kW
Max. AC Output Power	44 kW	55 kW	66 kW
Rated Output Voltage	480 V _{AC}	480/500 V _{AC}	480/500 V _{AC}
Output Voltage Range*	384-576 V _{AC}		
Grid Connection Type	3 Φ /PE		
Nominal AC Output Current @480 Vac	48.1 A	60.2/57.7 A	72.2/69.3 A
Rated Output Frequency	50/60 Hz		
Output Frequency Range*	47-52/57-62 Hz		
Power Factor	1 default (\pm 0.8 adjustable)		
Current THD	< 3 %		
SYSTEM			
Topology	Transformerless		
Max. Efficiency	98.8 %	99 %	
EU Efficiency	98.4 %	98.5 %	
Night Consumption	< 1 W		
ENVIRONMENT			
Protection Degree	IP65		
Cooling	Natural Convection Cooling	Intelligent Redundant Cooling	
Operating Temperature Range	-25 ° C to +60 ° C		
Storage Temperature Range	-40 ° C to +70 ° C		
Operating Humidity	0 - 100 %		
Operating Altitude	4000 m		
Audible Noise	<30 dBA @ 1 m	<60 dBA @ 1 m	
DISPLAY AND COMMUNICATION			
Display	LCD + LED		
Communication	Standard: RS485 (Modbus)		
MECHANICAL DATA			
Dimensions (W / H / D)	530 x 700 x 356.5 mm	630 x 700 x 357 mm	
Weight	58 kg	61 kg	63 kg
Installation Angle	90 degrees from horizontal		
DC Inputs	MC4		
SAFETY			
Safety and EMC Standard	IEC62109-1/-2		
Grid Standard	AS4777, NRS097		
Smart-Grid Features	Voltage-Ride Thru, Frequency-Ride Thru, Soft-Start, Volt-Var, Frequency-Watt, Volt-Watt		

*The "Output Voltage Range" and "Output Frequency Range" may differ according to specific grid standard.

* The specifications and key features contained in this datasheet may deviate slightly from our actual products due to the on-going innovation and product enhancement. Canadian Solar Inc. reserves the right to make necessary adjustment to the information described herein at any time without further notice.

Caution: For professional use only. The installation and handling of PV equipment requires professional skills and should only be performed by qualified professionals. Please read the safety and installation instructions before using the product.