

# InfiniSolar: On-Grid Inverter with Energy Storage



- Self-consumption and feed-in to the grid
- Programmable supply priority for PV, Battery or Grid
- User-adjustable battery charging current suits different types of batteries
- Programmable multiple operations modes: Grid tie, Off grid, and grid-tie with backup
- Built-in Timer for various mode of on/off operation
- Multiple communication for USB, RS-232, Modbus and SNMP
- Monitoring software for real time status display and control
- Custom-made firmware by ODM contract
- Parallel operation up to 6 units

ON-GRID INVERTER WITH ENERGY STORAGE

## InfiniSolar On-grid Inverter with Energy Storage Selection Guide

MODEL	InfiniSolar 3P 10KW	InfiniSolar 3P 15KW
<b>PHASE</b>	3-phase in / 3-phase out	
<b>MAXIMUM PV INPUT POWER</b>	14850 W	22500 W
<b>RATED OUTPUT POWER</b>	10000 W	15000 W
<b>MAXIMUM CHARGING POWER</b>	9600 W	15000 W
<b>GRID-TIE OPERATION</b>		
<b>PV INPUT (DC)</b>		
Nominal DC Voltage / Maximum DC Voltage	720 VDC / 900 VDC	720 VDC / 900 VDC
Start-up Voltage / Initial Feeding Voltage	320 VDC / 350 VDC	320 VDC / 350 VDC
MPP Voltage Range	400 VDC ~ 800 VDC	400 VDC ~ 800 VDC
Number of MPP Trackers / Maximum Input Current	2 / 2 x 18.6A	2 / A: 37.65A; B: 18.6A
<b>GRID OUTPUT (AC)</b>		
Nominal Output Voltage	230 VAC (P-N) / 400 VAC (P-P)	
Output Voltage Range	184 - 265VAC* per phase	184 - 264.5VAC per phase
Nominal Output Current	14.5A per phase	21.7A per phase
Power Factor	> 0.99	
<b>EFFICIENCY</b>		
Maximum Conversion Efficiency (DC/AC)	96%	
European Efficiency@ Vnominal	95%	
<b>OFF-GRID OPERATION</b>		
<b>AC INPUT</b>		
AC Start-up Voltage/Auto Restart Voltage	120 - 140 VAC per phase / 180 VAC per phase	
Acceptable Input Voltage Range	170 - 280 VAC per phase	
Maximum AC Input Current	40 A	
<b>PV INPUT (DC)</b>		
Maximum DC Voltage	900 VDC	900 VDC
MPP Voltage Range	400 VDC ~ 800 VDC	350 VDC ~ 850 VDC
Number of MPP Trackers/Maximum Input Current	2 / 2 x 18.6A	2 / A: 37.65A; B: 18.6A
<b>BATTERY MODE OUTPUT (AC)</b>		
Nominal Output Voltage	230 VAC (P-N) / 400 VAC (P-P)	230 VAC (P-N) / 400 VAC (P-P)
Output Waveform	Pure Sinewave	
Efficiency (DC to AC)	91%	91%
<b>HYBRID OPERATION</b>		
<b>PV INPUT (DC)</b>		
Nominal DC Voltage / Maximum DC Voltage	720 VDC / 900 VDC	720 VDC / 900 VDC
Start-up Voltage / Initial Feeding Voltage	320 VDC / 350 VDC	320 VDC / 350 VDC
MPP Voltage Range	400 VDC ~ 800 VDC	350 VDC ~ 850 VDC
Number of MPP Trackers/Maximum Input Current	2 / 2 x 18.6A	2 / A: 37.65A; B: 18.6A
<b>GRID OUTPUT (AC)</b>		
Nominal Output Voltage	230 VAC (P-N) / 400 VAC (P-P)	230 VAC (P-N) / 400 VAC (P-P)
Output Voltage Range	184 - 265 VAC* per phase	184 - 264.5 VAC per phase
Nominal Output Current	14.5 A per phase	21.7A per phase
<b>AC INPUT</b>		
AC Start-up Voltage / Auto Restart Voltage	120 - 140 VAC per phase / 180 VAC per phase	120 - 140 VAC per phase / 180 VAC per phase
Acceptable Input Voltage Range	170 - 280 VAC per phase	170 - 280 VAC per phase
Maximum AC Input Current	40 A	40 A
<b>BATTERY MODE OUTPUT (AC)</b>		
Nominal Output Voltage	230 VAC (P-N) / 400 VAC (P-P)	230 VAC (P-N) / 400 VAC (P-P)
Efficiency (DC to AC)	91%	
<b>BATTERY &amp; CHARGER</b>		
Nominal DC Voltage	48 VDC	
Maximum Charging Current	Default 60A, 10A - 200A (Adjustable)	Default 60A, 5A - 300A (Adjustable)
<b>GENERAL</b>		
<b>PHYSICAL</b>		
Dimension, D x W x H (mm)	167.2 x 500 x 622	219 x 650 x 820
Net Weight (kgs)	40	62
<b>INTERFACE</b>		
Communication Port	RS-232/USB	RS-232, USB and Dry contact
Intelligent Slot	Optional SNMP, Modbus and AS-400 cards available	
<b>ENVIRONMENT</b>		
Humidity	0 ~ 90% RH (Non-Condensing)	
Operating Temperature	-10 to 55°C	
Altitude	0 ~ 1000 m**	

\*These figures may vary depending on different AC voltage and country requirements.  
 \*\*Power derating 1% every 100 m when altitude is over 1000m.  
 Product specifications are subject to change without further notice.

CE VDE-AR-N 4105  
 VDE 0126-1-1  
 AS4777, AS/NZS3100, NRS-007-2-1 (only for InfiniSolar Plus 3KW)