



## AXIstorage Li SH



High-performance lithium-ions-energy storage for residential, e-mobility and commercial applications

### Advantages:



7,5 - 15 kWh useable capacity depending on the ordered degree of expansion with Energypacks each 2,5 kWh



Flexible configuration: up to max. 15 kWh useable capacity On-Grid



Permanent charging current of up to 29 A Permanent discharge current of up to 29 A



Up to 20 years of life time due to an optimized thermal management



10 years of time value replacement warranty



Handy sized Energypack with only 22 kg weight



## AXIstorage Li SH

#### **Electrical Data**

	←	<> SMA>		
		←	—— Kostal —	<b>→</b>
	3 Energypacks	4 Energypacks	5 Energypacks	6 Energypacks
Nominal Capacity	9,7 kWh	12,9 kWh	16,1 kWh	19,3 kWh
Useable Capacity	7,5 kWh	10,0 kWh	12,5 kWh	15,0 kWh
Nominal Voltage	155,0 V	207,0 V	258,0 V	310,0 V
Nominal Capacity	62,7 Ah	62,7 Ah	62,7 Ah	62,7 Ah
Charging Current	29 A	29 A	29 A	29 A
Discharge Current	29 A	29 A	29 A	29 A
Efficiency	>97 %	>97 %	>97 %	>97 %
Cooling	passive	passive	passive	passive
Range of Temperature	0 - 50 °C			
Max. Air Humidity (not condensing)	85 %	85 %	85 %	85 %

#### **Mechanical Data**

3 Energypacks	4 Energypacks	5 Energypacks	6 Energypacks	
Lithium (NMC)				
751 x 870 x 423 mm				
107 kg	129 kg	151 kg	173 kg	
IP21	IP21	IP21	IP21	
CE / UN 38.3 / IEC 62619				
	107 kg	Lithium 751 x 870 107 kg 129 kg IP21 IP21	751 x 870 x 423 mm 107 kg 129 kg 151 kg IP21 IP21 IP21	

# high quality german solar brand

#### Safety


- Double wall housing
- ${\boldsymbol{\cdot}}$  Elevated construction to protect against water damage
- · Monitoring of current, voltage and temperature
- Single cell monitoring
- State of charge determination and battery monitoring
  (SOC + SOH)
- Passive balancing


#### Delivery

- Case with BMS, connection cable and all communication cables up to and including degree of expansion with 6 Energypacks
- Energypacks each 2,5 kWh (3 6 units) please order separately

#### Compatibility

- SMA Sunny Boy Storage: 3.7 / 5.0 / 6.0
- Kostal Plenticore Plus





10 - 15 kWh

Technical data are subject to change without prior notice, errors excepted. The measurement tolerances are +/-3%. Please be aware: All technical data provided in our data sheets are property of Axitec Energy GmbH & Co.KG and intended for information purposes for our customers only. We cannot accept any guarantee of completeness or accuracy. These data are prohibited for any kind of commercial use.