

Enphase IQ 7A Microinverter

The high-powered smart grid-ready **Enphase IQ 7A Micro™** dramatically simplifies the installation process while achieving the highest system efficiency for systems with 60-cell and 72-cell modules.

Part of the Enphase IQ System, the IQ 7A Micro integrates with the Enphase Envoy-S™, Enphase IQ Battery™, and the Enphase Enlighten™ monitoring and analysis software.

The IQ Series Microinverters extend the reliability standards set forth by previous generations and undergo over a million hours of power-on testing, enabling Enphase to provide an industry-leading warranty.



High Power

- Peak output power 366 VA

Easy to Install

- Lightweight and simple
- Faster installation with improved, lighter two-wire cabling
- Built-in rapid shutdown compliant

Efficient and Reliable

- Optimized for high powered 60-cell and 72-cell modules
- Highest EU efficiency of 96.5%
- More than a million hours of testing
- Class II double-insulated IP67 enclosure

Smart Grid Ready

- Complies with advanced grid support, voltage and frequency ride-through requirements
- Envoy and Internet connection required
- Configurable for varying grid profiles

Enphase IQ 7A Microinverter

INPUT (DC)		IQ7A-72-2-INT	
Commonly used module pairings ¹		295 W–460 W +	
Module compatibility		60-cell and 72-cell PV modules	
Maximum input DC voltage		58 V	
Power point tracking voltage range ²		18 V–58 V	
Min/Max start voltage		30 V / 58 V	
Max DC short circuit current (module Isc) ³		15 A	
Overvoltage class DC port		II	
DC port backfeed current		0 A	
OUTPUT (AC)			
Peak output power		366 VA	
Maximum continuous output power		349 VA	
Nominal (L-N) voltage/range ⁴		230 V / 219–264 V	
Maximum continuous output current		1.52 A	
Nominal frequency		50 Hz	
Extended frequency range		45–55 Hz	
AC short circuit fault current over 3 cycles		5.8 Arms	
Maximum units per 20 A (L-N) branch circuit ⁵		11 (230 VAC)	
Overvoltage class AC port		III	
AC port backfeed current		18 mA	
Power factor setting		1.0	
Power factor (adjustable)		0.85 leading ...	0.85 lagging
EFFICIENCY			
EN 50530 (EU) weighted efficiency		96.5 %	
MECHANICAL			
Ambient temperature range		-40°C to +60°C	
Relative humidity range		4% to 100% (condensing)	
Connector type		MC4	
Dimensions (HxWxD)		212 mm x 175 mm x 30.2 mm (without bracket)	
Weight		1.08 kg (2.38 lbs)	
Cooling		Natural convection — No fans	
Approved for wet locations		Yes	
Pollution degree		PD3	
Enclosure		Class II double-insulated, corrosion resistant polymeric enclosure	
Environmental category / UV exposure rating		NEMA Type 6 / outdoor - IP67	
FEATURES			
Communication		Power Line Communication (PLC)	
Monitoring		Enlighten Manager and MyEnlighten monitoring options Compatible with Enphase Envoy-S	
Compliance		AS 4777.2, RCM, IEC/EN 61000-6-3, IEC/EN 62109-1 IEC/EN 62109-2	

1. No enforced DC/AC ratio. See the compatibility calculator at <https://enphase.com/en-us/support/module-compatibility>.

2. CEC peak power tracking voltage range is 38 V to 43 V.

3. Maximum continuous input DC current is 10.2A.

4. Voltage range can be extended beyond nominal if required by the utility.

5. Limits may vary. Refer to local requirements to define the number of microinverters per branch in your area.

To learn more about Enphase offerings, visit enphase.com