

# GS6P60-XXX



Australian brand, Australian guaranteed



Reliability fully conform to certification and regulatory standards



High performance under low light conditions cloudy days, mornings and evenings



High power output and highest conversion efficiency upto 15.98%




12 years material and workmanship warranty



13 years peak power output no less than 92.1%




25 years peak power output no less than 80.9%



### Electrical parameters at STC ( 1,000W/m<sup>2</sup>; AM 1.5; 25 °C)

Peak power (W) (Pm)	230	235	240	245	250	255	260
Power tolerance	0 ~ +3% (standard 0 ~+3%; ±3% optional)						
Open circuit voltage (V) (Voc)	36.75	37.08	37.17	37.2	37.47	37.54	38.2
Short circuit current (A) (Isc)	8.33	8.5	8.58	8.73	8.76	8.82	8.75
Max. power voltage (V) (Vmp)	29.64	29.83	29.96	30.14	30.34	30.19	29.9
Max. power current (A) (Imp)	7.76	7.88	8.02	8.13	8.24	8.25	8.7
Efficiency (%)	14.19%	14.51%	14.71%	15.02%	15.32%	15.63%	15.92%


### GS6P60-245W CURVE AM 1.5, 1000W/m<sup>2</sup>



### General characteristics

Front cover (material / thickness)	Low-iron tempered glass / 3.2mm
Frame (material / color)	Anodized aluminum alloy / silver
Cable (length / cross-sectional area)	900mm / 4mm <sup>2</sup>
Dimensions (L / W / H)	1640mm / 992mm / 40mm (35mm 45mm 50mm optional)
Weight	18.8kg

### AM 1.5, Module Temperature 25 °C



### Operating conditions

Max. system voltage	1000VDC
Max. series fuse rating	15A
Operating temperature range	-40°C to 85°C
Max. mechanical load	5400Pa
Fire safety class	Class C
Junction box (protection degree)	IP67

### Temperature ratings

NOCT	45°C(±2 °C)
Temperature coefficient of P <sub>MAX</sub>	-0.43%/ °C
Temperature coefficient of V <sub>oc</sub>	-0.32%/ °C
Temperature coefficient of I <sub>sc</sub>	0.047%/ °C



Gista Sunnyenergy Pty Ltd

www.gistasunnyenergy.com.au

support@gistasunnyenergy.com.au (Australia)

Tel : +61 (02) 9743 2288 Fax : +61 (02) 9743 6458

Australian brand. Australian guaranteed

